



DIESEL TRACTORS & MOWERS

Model

B1610

Engine	
Type	E-TVCS, Indirect injection, vertical, liquid cooled, 4 cycle diesel
DIN power	10.7 kW
SAE power	11.7 kW
PTO power	9.2 kW
No. of cylinders	3
Total displacement	719
Muffler	Fully enclosed
Air cleaner	Fully enclosed, dry paper element
Fuel tank	13 litres
Drive Train	
Driving method	4WD
Transmission speed	F6R2
max. travelling speed	with standard farm tyre 16.2 km/h
Brake type	Wet disc
PTO	
PTO type	Transmission driven with one way clutch
Rear PTO speed	540/1000 rpm
Mid Pto speed	2545 rpm
Hydraulic system	
Pump capacity	14.1 litres
Lift capacity (lower Link)	540 kg
Hydraulic circuit changeover unit	Standard
Dimensions	
Overall length	2035 mm
Overall Width	with standard farm tyre 927 mm
Overall height (steering)	1255 mm
Wheelbase	1270 mm
Ground clearance	270 mm

Tread (front)		with standard farm tyre 767 mm
Tread (rear)		711 - 1031 mm
Weight		522 kg
Tyre Farm	front	5 - 12
	rear	8 - 16
Tyre Turf	front	20 8.00 - 10
	rear	212 / 80D -15
Turning radius (with 4WD brake)		1.8 m
Other		
Steering		Manual
Water temp.gauge		Standard
Fuel gauge		Standard
Tachometer		Standard
Tool		Standard
Tool Box		Standard
Operator deck		Semi flat
Mower cutting width		1219 mm