



SPECIFICATIONS

MODEL		M5700	M8200 ROPS	M8200 Cab
		4WD Narrow	4WD Narrow with Bi-Speed Turn	
	Engine	EF2803-EA	V3300-TE	
	Type	E-TVCS liquid cooled, 4-cylinder diesel		
	PTO horsepower	HP (kW) 52 (38.8)	73 (54.5)	
	Net engine horsepower	HP (kW) 57 (42.5) @ 2800 rpm	82 (61.2) @ 2600 rpm	
	Bore and stroke	in. (mm) 3.43x3.64 (87x92)	3.86x4.33 (98x110)	
	Displacement	cu. In. (cc) 167.5 (2746)	202 (3318)	
	Air cleaner	Dry, dual element		
	Battery	12V, 700 CCA	12V, 1000 CCA	
	Cooling system	Heavy duty pressurized radiator		
Transmission/ Drive train	Clutch	Dry, single plate		
	Transmission	12 F X 12 R 4 Speed w/ Hi-Low & Creep Fully synchronized main		
	Differential lock	Rear Standard		
	Final drive	Inboard planetary		
	Brake	Mechanically operated, multi plate wet disc		
PTO System	Type	Live-hydraulic independent		
	Rear	540 rpm		
Hydraulics	Type	Open Center		
	Pump	Gear Pumps		
	Total pump output	gpm (l/min) 17.1 (64.7)	11.1 (41.6)	
	Remote output	gpm (l/min) 11.1 (41.6)		
	Hydraulic outlet			
	3-point hitch	Category I with Category II link ends		
	Hydraulic control system	Position with draft and mix control		
Capacities	Lift Capacity 24" behind LP	lbs. (kg) 3310 (1500)		
	Steering	Hydrostatic power steering		
	Fuel tank	gal. (l) 17.2 (65)	15.9 (60)	20.7 (78)
	Cooling system	qts. (l) 7.7 (7.3)	9.5 (9.0)	
	Engine oil	qts. (l) 8.5 (8.0)	11.3 (10.7)	
Dimensions & Weight	Transmission case	gal. (l) 10.6 (40.0)	8.7 (33)	
	Overall length (with 3P)	in. (mm) 134.1 (3405)	134.3 (3410)	
	Overall width (min tread)	in. (mm) 42.9 (1090)	40.6 (1030)	
	Overall height	in. (mm) 57.7 (1465) - ROPS Folded	87.8 (2230)	89.0 (2260)
	Wheelbase	in. (mm) 78.7 (2000)	78.7 (2000)	
	Ground clearance (Front Axle)	in. (mm) 14.0 (355)	12.2 (310)	
	Turning radius w/brake, w/Bi-speed	ft. (m) 9.5 (2.9)	10.5 (3.2)	
Tire Size	Weight	lbs. (kg) 3792 (1720)	4080 (1850)	4740 (2150)
	Ag Standard	Front/Rear	8.0-16 R1 / 12.4R24 Radial	

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.